



▶ MicroPulse™ | External Mount/Perimeter Lights

FEATURES

- Low profile for discreet mounting.
- Models available for hood, grille, and surface mount applications.
- Superior warning with high-power LEDs.
- Solid and split-color models are available.
- Single/multi-unit synchronization.
- Dual-color hood/grille models (MPS652)
- Multi-voltage input of 12-24 VDC.
- Brackets available for multiple mounting options.
- Three-year LED warranty.

APPROVALS

MicroPulse 6 models

- SAE J845
- SAE J595

MicroPulse 3 models

- SAE J845
- SAE J595

High-performance LEDs provide first-responder and work truck vehicles with superior auxiliary warning capability. Extremely compact MicroPulse perimeter lights feature an advanced high-output LED lighthouse for additional warning around the outside of your vehicle.

MicroPulse's stealthy, low-profile design accommodates the full range of hood-, grille- and surface-mount applications. Available in both solid and split-color models, MicroPulse lights can be programmed to operate as single unit or in synchronization with multiple MicroPulse lighthouses. Built-in flash patterns enable multiple vehicle perimeter lights to be either synchronized in the same pattern or in opposite sequence.

MicroPulse delivers optimum flexibility through a choice of different colors and color combinations.

Colors include red, blue, white and amber as well as split-color models in red/blue, blue/amber and red/white combinations. Other features include a fully encapsulated water-proof housing, and multi-voltage input of 12-24 VDC.



MPS6 shown as surface mount



MPS3 shown as surface mount



MPS6 shown with grille/hood mount



MPS3 shown with grille/hood mount



S P E C I F I C A T I O N S

MPS300 and MPS350 Models

Specifications

Voltage	12-24 VDC
Current Draw	0.2 Amps at 12 VDC 0.11 Amps at 24 VDC
Operating temp	-40°C to 80°C

Physical Specifications

	Hood Version	Surface Mount
Height	0.94 in (2.4 cm)	1.1 in (2.8 cm)
Length	2.5 in (6.5 cm)	3.4 in (8.6 cm)
Depth	1.5 in (3.7 cm)	0.6 in (1.6 cm)

Ship Weight

0.5 lbs (0.23 kg)

Patterns and Flash Rates

Flash Pattern	Description	Flash Pattern	Description
1	Random	11	Single H/L
2	Steady	12	Single Triple Quint
3	Single	13	N/A
4	Mega	14	N/A
5	Double	15	N/A
6	Triple	16	N/A
7	Quad	17	N/A
8	Quint	18	N/A
9	8 Flash	19	N/A
10	Single-Quad		

MPS300/MPS350 Compliance Chart

Color	Flash Patterns	SAE J845	SAE J595	CA T13
Red	2, 4, 5, 7	Class 1	Class 1	-
Red	6 & 8	Class 2	Class 2	-
Blue	2, 4-8	Class 2	Class 2	-
Amber	2, 4-8	Class 2	Class 2	-
White	2, 4-8	Class 2	Class 2	-
Red	7	-	-	Class B
Blue	-	-	-	N/C
Amber	-	-	-	N/C
White	-	N/C	Class 2	N/C

S P E C I F I C A T I O N S

MPS600 and MPS650 Models

Specifications

Voltage	12-24 VDC
Current Draw	0.55 Amps at 12 VDC 0.26 Amps at 24 VDC
Operating temp	-40°C to 80°C

Physical Specifications

	Hood Version	Surface Mount
Height	0.94 in (2.4 cm)	1.1 in (2.8 cm)
Length	4.2 in (10.8 cm)	5.0 in (12.7 cm)
Depth	1.7 in (4.3 cm)	0.68 in (1.73 cm)

Ship Weight

0.75 lbs (0.34 kg)

Patterns and Flash Rates

Flash Pattern	Description	Flash Pattern	Description
1	Double(all)	11	Steady 4(all)
2	Quad(all)	12	Quad(all)
3	Quint(all)	13	Quint(all)
4	Mega(all)	14	Mega(all)
5	Ultra(all)	15	Ultra(all)
6	Single Quad(all)	16	Single Quad(all)
7	Single H/L(all)	17	Single H/L(all)
8	Steady 2(CA)	18	Steady 2(CA)
9	Steady 4(all)	19	Steady 4(all)
10	Steady 4(all)		

MPS600/MPS650 Compliance Chart

Color	Flash Patterns	SAE J845	SAE J595	CA T13
Red	9-12, 14	Class 1	Class 1	-
Blue	9, 10, 12	Class 1	Class 1	-
Blue	11 & 14	Class 2	Class 2	-
Amber	9-12, 14	Class 1	Class 1	-
White	9, 10, 12, 14	Class 1	Class 1	-
White	11	Class 1	Class 2	-
Red	9	-	-	Class B
Blue	9	-	-	Class B
Amber	9	-	-	Class B
White	-	N/C	Class 2	N/C

*All LED's operating in sync

Select Model

Hood/Grille Mount, 3-LED light head, Black housing, 12-24VDC

- MPS350-R 3-LED light head, Red
- MPS350-B 3-LED light head, Blue
- MPS350-A 3-LED light head, Amber
- MPS350-W 3-LED light head, White

Hood/Grille Mount, 6-LED light head, Black housing, 12-24VDC

- MPS650-RR 6-LED light head, Red/Red
- MPS650-RB 6-LED light head, Red/Blue
- MPS650-BB 6-LED light head, Blue/Blue
- MPS650-BA 6-LED light head, Blue/Amber
- MPS650-RW 6-LED light head, Red/White
- MPS650-WW 6-LED light head, White/White
- MPS650-AA 6-LED light head, Amber/Amber
- MPS650-BW 6-LED light head, Blue/White
- MPS650-AW 6-LED light head, Amber/White

Surface Mount, 6-LED light head, Black housing, 12-24VDC

- MPS600-RR 6-LED light head, Red/Red
- MPS600-RB 6-LED light head, Red/Blue
- MPS600-BB 6-LED light head, Blue/Blue

Dual-Color, hood/grille mount light-head with black bezel, 12-24 VDC, 12-LEDs total (6 per color)

- MPS652-BA 12-LED light-head, Blue/Amber
- MPS652-BR 12-LED light-head, Blue/Red
- MPS652-BW 12-LED light-head, Blue/White
- MPS652-RA 12-LED light-head, Red/Amber
- MPS652-RW 12-LED light-head, Red/White
- MPS652-WA 12-LED light-head, White/Amber

MicroPulse 3 Brackets

- MPSM3-LB L-Bracket for (1) MPS300
- MPSM3-DS L-Bracket for (2) MPS300, stacked
- MPSM3-BOOT Rubber boot mount for (1) MPS300
- MPSM3-DL L-Bracket for (2) MPS300, side-by-side
- MPSM3-SB Swivel Mount Bracket for (1) MPS300
- MPSM3-BOOTKIT (2) Rubber boot mounts, (2) boot mounting plates for (2) MPS300

MicroPulse 6 Brackets

- MPSM6-LB L-Bracket for (1) MPS600
- MPSM6-DS L-Bracket for (2) MPS600, stacked
- MPSM6-BOOT Rubber boot mount for (1) MPS600
- MPSM6-DL L-Bracket for (2) MPS600, side-by-side
- MPSM6-SB Swivel Mount Bracket for (1) MPS600
- MPSM6-BOOTKIT (2) Rubber boot mounts, (2) boot mounting plates for (2) MPS600



**Optional Accessories
MicroPulse 3 Brackets**



MPSM3-LB



MPSM3-DS



MPSM3-BOOT



MPSM3-DL



MPSM3-SB



MPSM3-BOOTKIT



MPSM3-SPACRKT

MicroPulse 6 Brackets



MPSM6-LB



MPSM6-DS



MPSM6-DL



MPSM6-SB



MPSM6-BOOT



MPSM6-BOOTKIT



MPSM6-SPACRKT