



VSLR1-R



VSLR1-R1A02

## ▶ IVP VSLR | LED Beacon

### FEATURES

- NFPA Compliant models available.
- Patented Solaris LED Rotator for a true 360-degrees of sweeping coverage.
- Compliments Vision SLR lightbars.

### REPLACEMENT PARTS

- Meets NFPA requirements when used as part of a complete system.

Federal Signal has combined the superior light output of a rotator with the advantages of LEDs to create the first true LED beacon in the marketplace, the IVP SLR.

Featuring the patented Solaris LED Rotator, the IVP SLR creates a burst of illumination with the benefits of a rotator to create a sweep of light unmatched by flashing lights.

The IVP VSLR is available in two styles that compliment Federal Signal's Vision SLR lightbars. The VSLR1 features red or amber LEDs and may be used as part of an NFPA lighting package. The VSLR1-R1A02 is NFPA compliant and features a red LED rotator and an IMPAXX 6 light in an attractive housing.

**Specify Model**

VSLR1-R1A02	Red LEDs, Red dome, (1) Amber IPX6, Clear lens
VSLR1-R2A02	Red LEDs, Clear dome, (1) Amber IPX6, Clear lens
VSLR1-R1	Red LEDs, Red dome
VSLR1-R2	Red LEDs, Clear dome
VSLR1P-R1	Red LEDs, Red dome, passenger side
VSLR1D-R1	Red LEDs, Red dome, driver side
VSLR1P-R2	Red LEDs, clear dome, passenger side
VSLR1D-R2	Red LEDs, clear dome, driver side

Specifications VSLR1		
	VSLR1	VSCLR1-R1A02
Voltage	12/24 VDC	12 VDC
Amp Draw	-30°C to +65°C	-30°C to +65°C
Physical Specifications		
Height	4.5 in (11.4 cm)	5.0 in (12.7 cm)
Length	7.3 in (18.5 cm)	7.3 in (18.5 cm)
Depth	10.0 in (25.4 cm)	10.0 in (25.4 cm)
Ship Weight		
	5.5 lbs (2.5 kg)	6.0 lbs (2.7 kg)

